UNI-STRIPP

UNIVERSAL STRIPPER FOR ALL PAINTS AND COATINGS

DESCRIPTION

UNI-STRIPP universal stripper is an environmentally safe paint and coatings stripper designed to remove a wide variety of paints, stains, and varnishes which are oil or water-based including, latex alkyds, stains, enamels, lacquers and clear paints. Unlike other paint removers, UNI-STRIPP can remove more difficult coatings such as two component epoxy or urethane sealers from concrete surfaces. UNI-STRIPP is also very effective on mastic adhesives and glues.

FEATURES

- 100% Bio-degradable
- VOC compliant
- Low odor
- Acid free
- Leaves no residue
- Methylene chloride free
- Can remove multiple layers
- Can be cleaned with water
- Can cling to vertical surfaces

TECHNICAL INFORMATION

Composition: Contains Dibasic esters, n-methyl-2-pyrrolidone, and citrus oil extracts.

Viscosity: 60 KU @ 70 F

PACKAGING

One gallon and five gallon units

SHELF LIFE

3 years in original, unopened containers

COVERAGE

50 sq. ft/gal @ 1/32 "



INCRETE SYSTEMS

1611 Gunn Hwy. Odessa, FL 33556

Phone: 813-886-8811 - Toll-Free: 800-752-4626 - Fax: 813-920-1516

www.increte.com





UNI-STRIPP

UNIVERSAL STRIPPER FOR ALL PAINTS AND COATINGS

DIRECTIONS FOR USE

UNI-STRIPP is applied to the coating surface at approximately 1/32 inches.

Application can be by brush, roller or trowel. For best results cover all applications with plastic. A small test patch of the coated surface should be applied first. This is to determine the dwell time needed to soften and remove the coating. Normally two-component epoxy systems need an extended dwell time. Thermoplastic acrylics often require less than 30-minute dwell times.

UNI-STRIPP may be worked in with a stiff bristled broom for added effectiveness. Loosened coatings can then be scraped or rinsed with a power washer. Control rinse water runoff. Re-apply stripper as needed.

PRECAUTIONS/LIMITATIONS

SAFETY PRECAUTIONS: Use with adequate ventilation. Avoid prolonged breathing vapors and contact with skin.

DANGER: Harmful if swallowed, contains petroleum distillates. If swallowed, do not induce vomiting. Call physician immediately.

For professional use only. Keep away from Children. Always consult MSDS prior to use.

WARRANTY All recommendations, statements and technical data contained herein based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. User shall rely on his own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his use of the product of this manufacturer which proves to be defective. Neither seller nor manufacturer shall be liable to the buyer or any third person having any injury, loss or damage directly resulting from use of or inability to use the product. Recommendations or statements other than those contained in written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller.

IMPORTANT NOTICE: THESE PRODUCTS ARE SOLD SUBJECT ONLY TO THE EXPRESSED WARRANTIES CONTAINED HEREIN. ADDITIONAL WARRANTIES, EXPRESSED OR IMPLIED, AND ANY WARRANTY OF MERCHANT ABILITY IS HEREBY EXCLUDED. BUYER AGREES THAT SELLER ASSUMES NO LIABILITY FOR CONSEQUENTIAL DAMAGES OF ANY KIND, WHICH RESULT FROM THE USE OR MISUSE OF THE MERCHANDISE SOLD HEREUNDER. IN THE EVENT THAT THE BUYER PROVES THAT ANY GOODS RECEIVED DO NOT CONFORM TO THE SPECIFICATIONS AGREED TO BETWEEN THE PARTIES OR IF THE BUYER PROVES THAT SUCH GOODS WERE DEFECTIVELY MANUFACTURED. THE BUYER'S REMEDIES SHALL BE LIMITED TO EITHER THE RETURN OF THE GOODS AND REPAYMENT OF THE PURCHASE PRICE OR REPLACEMENT OF THE NON-CONFORMING GOODS AT THE OPTION OF THE SELLER. SUCH REMEDY BEING EXCLUSIVE OF ALL OTHERS AND THE SOLE REMEDY AVAILABLE TO THE BUYER, HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES.