

# MATTE ADD

## FLATTENING ADDITIVE FOR ACRYLIC SEALERS

### DESCRIPTION

**Increte Systems MATTE ADD** is a colorless, finely graded, polypropylene additive for sealers and coatings, leaving a low gloss finish. MATTE ADD may be stirred into standard acrylic sealers to turn any acrylic sealer into a low gloss coating. Unlike many silica additives, Increte **MATTE ADD** will stay suspended in solution longer, without continuous stirring.

### FEATURES

- Provides satin or matte finish
- Stirs in readily
- Neutral buoyancy—doesn't settle or float quickly
- Works in solvent and water based acrylic systems
- For use with Increte Systems Clear Seals, Cure-Cretes, Paver Sealers, Concrete Stain Sealers in Solvent Based, Water Based or Low VOC.

### TECHNICAL INFORMATION

**Composition:** Polypropylene powder.  
**Particle Size:** 325 Mesh

### PACKAGING

1 pound or 15 pound units

### SHELF LIFE

4+ years in original, unopened containers

### COVERAGE

MATTE ADD is added at 8 fluid ounces (1 scoop) per gallon or one pound per five gallons of sealer.



Decorative Concrete  
Technology

#### INCRETE SYSTEMS

1611 Gunn Hwy. Odessa, FL 33556

Phone: 813-886-8811 - Toll-Free: 800-752-4626 - Fax: 813-920-1516

[www.increte.com](http://www.increte.com)

A Division of The Euclid Chemical Company An **RPM** Company

# MATTE ADD

## FLATTENING ADDITIVE FOR ACRYLIC SEALERS

### DIRECTIONS FOR USE

#### APPLICATION PROCESS

MATTE ADD can be used in most acrylic sealers and coatings where lower gloss is desired. MATTE ADD can be used indoors or outdoors, especially over decorative concrete surfaces.

**Standard Dosage** – 8 fl.oz per gallon, or 1 pound per 5 gallon pail. Dosage may be varied to achieve the desired effect. Dosages above 12 fl.oz per gallon may cause excessive viscosity build. Performance and results will vary based on sealer choice and application conditions. Perform jobsite tests for optimum results.

**Procedure** – Apply first coat of sealer **without** the addition of **MATTE ADD**.

Mix sealer or coating to proper consistency. For best results, pull off 20-30% of the material and slowly add prescribed amount of **MATTE ADD** while mechanically mixing and mix until properly dispersed. Then return flattened material to container and re-mix.

Once first coat of sealer has dried, apply flattened sealer in an inconspicuous area and allow to dry to verify desired effect.

Apply in thin, uniform coats. If material is allowed to sit, re-mix before use.

Results may vary depending on coating, substrate and application techniques.

### PRECAUTIONS/LIMITATIONS

When finely divided and suspended in air, this product could be flammable. Keep away from heat, sparks, and open flame. Use with adequate ventilation.

**KEEP AWAY FROM CHILDREN.**

**WARRANTY** All recommendations, statements and technical data contained herein based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. User shall rely on his own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his use of the product of this manufacturer which proves to be defective. Neither seller nor manufacturer shall be liable to the buyer or any third person having any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations or statements other than those contained in written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller.

**IMPORTANT NOTICE:** THESE PRODUCTS ARE SOLD SUBJECT ONLY TO THE EXPRESSED WARRANTIES CONTAINED HEREIN. ADDITIONAL WARRANTIES, EXPRESSED OR IMPLIED, AND ANY WARRANTY OF MERCHANTABILITY IS HEREBY EXCLUDED. BUYER AGREES THAT SELLER ASSUMES NO LIABILITY FOR CONSEQUENTIAL DAMAGES OF ANY KIND, WHICH RESULT FROM THE USE OR MISUSE OF THE MERCHANDISE SOLD HEREUNDER. IN THE EVENT THAT THE BUYER PROVES THAT ANY GOODS RECEIVED DO NOT CONFORM TO THE SPECIFICATIONS AGREED TO BETWEEN THE PARTIES OR IF THE BUYER PROVES THAT SUCH GOODS WERE DEFECTIVELY MANUFACTURED, THE BUYER'S REMEDIES SHALL BE LIMITED TO EITHER THE RETURN OF THE GOODS AND REPAYMENT OF THE PURCHASE PRICE OR REPLACEMENT OF THE NON-CONFORMING GOODS AT THE OPTION OF THE SELLER. SUCH REMEDY BEING EXCLUSIVE OF ALL OTHERS AND THE SOLE REMEDY AVAILABLE TO THE BUYER, HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES.