

ANTIQUÉ RELEASE

POWDERED STAMP TOOL RELEASING AGENT

DESCRIPTION

INCRETE ANTIQUE RELEASES are an economical alternative to traditional releases. ANTIQUE RELEASES contain a specially formulated releasing agent that forms a moisture barrier between the stamping tools and wet concrete to facilitate the release of imprinting tools. It is a dry shake material applied directly on top of the concrete, COLOR HARDENER, or COLOR-CRETE prior to stamping. The colored antique releases contain integrated iron oxide pigments to add color and depth to the stamped surface.

PRIMARY APPLICATIONS

For use on stamped concrete products only.

FEATURES/BENEFITS

INCRETE ANTIQUE RELEASES are a must on textured concrete, providing the barrier essential to prevent suction that detracts from a finished product, thus greatly reduces the need for touch-up. By using a colored release, a rich looking antique effect is achieved. There are various combinations of colors that will give the two-tone effect by accenting the highlights. The darker color applied on top of the color hardener recesses into grout lines and deeper textures.

TECHNICAL INFORMATION

Available in 30 standard colors (see Increte Standard Color Charts) plus clear. Special colors can be matched by request (minimum order requirements apply).

PACKAGING

35 lb. Pail

SHELF LIFE

4 years in unopened pail

COVERAGE

One-35 lb. Pail will cover approximately 800-1000 square feet depending on job conditions and application methods.



Decorative Concrete
Technology

INCRETE SYSTEMS

1611 Gunn Hwy. Odessa, FL 33556

Phone: 813-886-8811 - Toll-Free: 800-752-4626 - Fax: 813-920-1516

www.increte.com

A Division of The Euclid Chemical Company An **RPM** Company

ANTIQUE RELEASE

POWDERED STAMP TOOL RELEASING AGENT

DIRECTIONS FOR USE

PREPARATION: All surrounding areas should be protected from contamination of the dust created by the broadcast method of application. Poly-sheeting is recommended for masking.

WHEN TO APPLY: After all color hardener is applied and/or final troweling is completed, and when no bleed water is on the surface.

BROADCASTING PROCEDURE: Material is a dust hazard, use a dust mask to prevent inhalation. Before broadcasting release, empty half of the contents of a pail into a clean, dry container and aerate material to loosen any compaction before broadcasting onto surface. Apply lightly and evenly over area using a casting motion. Use caution in windy conditions. Two applications may be required for uniform coverage. For optimal result, dash brush may be used to broadcast release.

FINISHING

After the concrete has set and dried, remove the excess color by rinsing with water (no additives). Take care not to wash off completely. Use a lighter, quicker rinsing action for the grout lines and deeper indentations. Removing most of the release from the high spots, and leaving more of the color in the deeper areas will enhance antique effect for a beautiful, more natural finish.

After the concrete has been washed and dried thoroughly, use one of INCRETE'S Clear Sealers to protect the surface and seal color permanently. Refer to appropriate tech-data sheets for application methods and coverage rates.

CLEAN-UP

Clean hands, tools and equipment with warm soapy water.

PRECAUTIONS/LIMITATIONS

Keep any unused product in a clean and dry sealed-container. Irritant to eyes and skin, Do not swallow. If eye or skin contact is made, flush with water for 15 minutes. If swallowed, dilute with water. Wear rubber gloves and splash proof goggles.

WARRANTY All recommendations, statements and technical data contained herein based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. User shall rely on his own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his use of the product of this manufacturer which proves to be defective. Neither seller nor manufacturer shall be liable to the buyer or any third person having any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations or statements other than those contained in written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller.

IMPORTANT NOTICE: THESE PRODUCTS ARE SOLD SUBJECT ONLY TO THE EXPRESSED WARRANTIES CONTAINED HEREIN. ADDITIONAL WARRANTIES, EXPRESSED OR IMPLIED, AND ANY WARRANTY OF MERCHANT ABILITY IS HEREBY EXCLUDED. BUYER AGREES THAT SELLER ASSUMES NO LIABILITY FOR CONSEQUENTIAL DAMAGES OF ANY KIND, WHICH RESULT FROM THE USE OR MISUSE OF THE MERCHANDISE SOLD HEREUNDER. IN THE EVENT THAT THE BUYER PROVES THAT ANY GOODS RECEIVED DO NOT CONFORM TO THE SPECIFICATIONS AGREED TO BETWEEN THE PARTIES OR IF THE BUYER PROVES THAT SUCH GOODS WERE DEFECTIVELY MANUFACTURED. THE BUYER'S REMEDIES SHALL BE LIMITED TO EITHER THE RETURN OF THE GOODS AND REPAYMENT OF THE PURCHASE PRICE OR REPLACEMENT OF THE NON-CONFORMING GOODS AT THE OPTION OF THE SELLER. SUCH REMEDY BEING EXCLUSIVE OF ALL OTHERS AND THE SOLE REMEDY AVAILABLE TO THE BUYER, HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES.